

Appl. No. 10/604,599  
Amdt. dated July 6, 2006  
Reply to Office action of May 9, 2006

## AMENDMENTS TO THE CLAIMS

### Listing of Claims:

Claims 1 – 20 (cancelled)

5

#### 21. (Previously Presented)

A color conversion apparatus for converting an input color being in a first color space to an output color being in a second color space, wherein both the input color and the output color include a plurality of color elements, the apparatus comprising:

10 a first lookup table being coupled to a first color element of the input color for outputting a corresponding first converted color element;

a second lookup table being coupled to a second color element of the input color for outputting a corresponding second converted color element; and

15 an adder circuit being coupled to the first lookup table and the second lookup table for summing the first converted color element, the second converted color element and a target color element to thereby generate a color element of the output color;

wherein both of the input color and the output color are in a RGB format including R, G, and B components respectively representing red, green, and blue colors, and both of the

20 target color element and the color element of the output color relate to the same component, that is the R, G, or B component.

#### 22. (Previously Presented) The apparatus of claim 21, further comprising:

25 a gamma correction circuit being coupled to a third color element of the input color for generating the target color element;

wherein the adder circuit is further coupled to the gamma correction circuit for summing the first converted color element, the second converted color element, and the target color element to thereby generate the color element of the output

Appl. No. 10/604,599  
Amdt. dated July 6, 2006  
Reply to Office action of May 9, 2006

color being in the second color space.

23. (Previously Presented) The apparatus of claim 21, wherein the adder circuit is for  
summing the first converted color element, the second converted color element, and  
the target color element to thereby generate a temporary color element.
24. (Previously Presented) The apparatus of claim 23, further comprising a gamma  
correction circuit being coupled to the adder circuit for performing a gamma  
correction operation on the temporary color element outputted by the adder to  
thereby generate the color element of the output color being in the second color  
space.
25. (Previously Presented) The apparatus of claim 21, wherein the first lookup table  
maps a plurality of values for the first color element of the input color to a single  
corresponding value of the first converted color element, and the second lookup  
table maps a plurality of values for the second color element of the input color to a  
single corresponding value of the second converted color element.
26. (Previously Presented) The apparatus of claim 25, wherein within the first lookup  
table, eight values of the first color element of the input color map to a single  
corresponding value of the first converted color element; and within the second  
lookup table, eight values of the second color element of the input color map to a  
signal corresponding value of the second converted color element.
27. (Previously Presented) The apparatus of claim 21, wherein the first lookup table is  
indexed by using a number of bits from values of the first color element of the input  
color; and the second lookup table is indexed by using the number of bits from  
values of the second color element of the input color.

Appl. No. 10/604,599  
Amdt. dated July 6, 2006  
Reply to Office action of May 9, 2006

28. (Previously Presented) The apparatus of claim 27, wherein the number of bits comprise a number of most significant bits.
- 5 29. (Previously Presented) The apparatus of claim 21, wherein both the first lookup table and the second lookup table comprise a plurality of sub-tables for storing a relationship between the first color space and the second color space.
- 10 30. (Previously Presented) The apparatus of claim 21, wherein the apparatus is utilized in a liquid crystal display (LCD).
31. (Previously Presented)  
A method for converting an input color being in a first color space to an output color being in a second color space, wherein both the input color and the output color  
15 include a plurality of color elements, the method comprising:  
looking up a first color element of the input color in a first lookup table to determine a corresponding first converted color element;  
looking up a second color element of the input color in a second lookup table to determine a corresponding second converted color element; and  
20 summing the first converted color element, the second converted color element and a target color element to thereby generate a color element of the output color;  
wherein both of the input color and the output color are in a RGB format including R, G, and B components respectively representing red, green, and blue colors, and both the target color element and the color element of the output color relate to the same  
25 component, that is R, G, or B component.
32. (Previously Presented) The method of claim 31, further comprising:  
performing a gamma correction operation on a third color element of the input color

Appl. No. 10/604,599  
Amdt. dated July 6, 2006  
Reply to Office action of May 9, 2006

to generate the target color element; and  
summing the first converted color element, the second converted color element, and  
the target color element to thereby generate the color element of the output color  
being in the second color space.

5

33. (Previously Presented) The method of claim 31, further comprising summing the  
first converted color element, the second converted color element, and the target  
element to thereby generate a temporary color element.

10 34. (Previously Presented) The method of claim 33, further comprising performing a  
gamma correction operation on the temporary color element of the output color to  
thereby generate the color element of the output color being in the second color  
space.

15 35. (Previously Presented) The method of claim 31, wherein the first lookup table  
maps a plurality of values for the first color element of the input color to a single  
corresponding value of the first converted color element, and the second lookup  
table maps a plurality of values for the second color element of the input color to a  
single corresponding value of the second converted color element.

20

36. (Previously Presented) The method of claim 35, wherein within the first lookup  
table, eight values of the first color element of the input color map to a single  
corresponding value of the first converted color element; and within the second  
lookup table, eight values of the second color element of the input color map to a  
signal corresponding value of the second converted color element.

25

37. (Previously Presented) The method of claim 31, further comprising:

5

Appl. No. 10/604,599  
Amdt. dated July 6, 2006  
Reply to Office action of May 9, 2006

indexing the first lookup table by a number of bits from values of the first color element of the input color; and

5 indexing the second lookup table by the number of bits from values of the second color element of the input color.

38. (Previously Presented) The method of claim 37, wherein the number of bits comprise a number of most significant bits.

10 39. (Previously Presented) The method of claim 31, further comprising storing a relationship between the first color space and the second color space within a plurality of sub-tables in both the first lookup table and the second lookup table.

15 40. (Previously Presented) The method of claim 31, wherein the method is utilized in a liquid crystal display (LCD).